Forest Products Journal Index . . . 1972

Articles are listed in two ways: by subject and by author. The Subject Index is organized according to the four major FPRS Divisions — Products, Management, Processes, and Fundamental Disciplines. Under each Division heading, subject headings are listed in accordance with the FPRS Technical Committee structure. Articles are filed alphabetically under the appropriate subject heading(s).

The Author Index contains an entry for each author, with complete information listed under the senior author; listings for co-authors refer back to the senior author.

Reprints of all articles listed in the index may be obtained. The reprint order number and the cost per single copy are listed in both sections. Prices are based on 20 cents per printed page, with a $1.50 maximum charge per reprint. Special bulk rates are available. Check or money order must accompany all orders.

FPRS Subject Index . . . Vol. 22, 1972

PRODUCTS DIVISION

Softwood Lumber

Boring Deep Holes in Southern Pine, G. E. Woodson and C. W. McMillin, 4:49 (No. 4700—$1.00)

Can the Electrical Moisture Meter be Used for Testing Lumber to Meet American Lumber Standards? W. J. Delmhorst, 12:40 (No. 4732—$.60)

Drying Southern Pine at 240°F.—Effects of Air Velocity and Humidity, Board Thickness and Density, P. Koch, 9:62 (No. 4821—$1.20)

Dynamic Compression Results in Greatly Increased Creosote Retention in Spruce Heartwood, M. Y. Cech and D. R. Huffman, 4:21 (No. 4681—$1.00)

Effect of Single Knots on Tensile Strength of 2 by 8 Douglas-Fir Dimension Lumber, R. H. Kunesh and J. W. Johnson, 1:32 (No. 4649—$1.00)

Kiln- and Boulton-Drying Douglas-Fir Pole Sections at 220° to 290°F., R. D. Graham and R. J. Womack, 10:50 (No. 4806—$1.20)

Kiln Drying of Southern Pine Poles: Results of Laboratory and Field Studies, W. S. Thompson and R. R. Stevens, 3:17 (No. 4688—$1.50)

Moisture Content of Southern Pine as Related to Thrust, Torque, and Chip Formation in Boring, C. W. McMillin and G. E. Woodson, 11:55 (No. 4820—$1.00)

Nondestructive Parameters of Lodgepole Pine Dimension Lumber in Bending, M. R. O'Halloran, J. Bodig, and D. C. Bowden, 2:44 (No. 4654—$1.50)

Plasticizing Distortion-Prone Softwood Studs Prior to High Temperature Seasoning, J. F. G. Mackay and B. L. Rumball, 6:27 (No. 4711—$.40)

Predicting Moisture Content in Douglas-Fir and Ponderosa Pine Boards, D. P. Lowery, 12:35 (No. 4861—$1.00)

Reducing Variability in Final Moisture Content of Kiln-Dried Western Hemlock Lumber, C. J. Kozlik and L. W. Hamlin, 7:24 (No. 4781—$1.50)

Resistance Moisture Meter Correction Factors for Western Softwood Species, M. Salamon, 12:46 (No. 4847—$.40)

Steaming under Restraint to Remove Warp in Dried Softwood Studs, W. A. Dost and D. G. Arganbright, 3:42 (No. 4690—$.60)

Shear Strength of High-Temperature Heat-Treated Douglas-Fir Lumber Laminated with Phenol-Resorcinol Adhesives, J. D. Bohlen, 12:17 (No. 4822—$1.50)

Suitability of Commercial Hem-Fir for Preservative-Treated Lumber and Glued-Laminated Beams, G. Bramhall and P. A. Cooper, 2:33 (No. 4666—$1.00)

Hardwood Lumber

Azeotropic Drying of Yellow Birch and Hard Maple Lumber, D. R. Huffman, F. Pfaff, and S. M. Shah, 8:53 (No. 4757—$.80)

Drying of Predrilled Aspen Lumber, R. Erickson and L. Demaree, 11:48 (TN-230—$.60)

Germany's Parquet Flooring Industry—The Struggle to Survive, H. Kubler and J. Lempelius, 10:14 (No. 4929—$.60)

Kiln-Drying Aspen Studs, D. R. Huffman, 10:21 (TN-232—$.60)

Kiln-Drying of Presurfaced 4/4 Appalachian Oak, D. G. Cuppett and E. P. Craft, 6:36 (No. 4752—$1.20)

New Kiln Schedule for Presurfaced Oak Lumber, J. M. McMillen and R. C. Baltes, 5:19 (No. 4769—$1.50)

Sawing Method Effect on the Production of Cherry Lumber, P. C. Kersavage, 8:33 (No. 4780—$1.50)

Sawing Pattern and Bolt Quality Effects on Yield and Productivity from Yellow Birch, D. W. Bousquet, 11:39 (No. 4793—$1.50)

Sawing Pattern Effect on the Yield of Lumber and Furniture Components from Medium and Low Grade Hard Maple Logs, S. M. Pnevmaticos and D. W. Bousquet, 3:34 (No. 4652—$1.50)

Treated Wood Products

Changes in Creosote Content of Immersed Wood, D. J. Miller, 3:25 (No. 4621—$1.50)

Characteristics of Preservative Solutions which Influence their Penetration of Wood, D. D. Nicholas, 5:31 (No. 4730—$1.20)

Condition of Preservative-Treated Cooling Tower Slats After 10-Year Service, L. R. Gjovik, B. A. Bendtsen, and H. G. Roth, 4:35 (No. 4674—$1.20)

Development of an All-Weather, Fire-Retardant Treatment, B. H. Shunk, 2:12 (No. 4682—$.80)

Development of Respirometry as a Method for Evaluating Wood Preservatives, E. A. Behr, 4:26 (No. 4685—$1.20)

Discontinuous Treatment for Flame-Spread Control, W. T. Nearn and R. A. Megraw, 7:47 (No. 4735—$1.20)

Dynamic Compression Results in Greatly Increased Creosote Retention in Spruce Heartwood, M. Y. Cech and D. R. Huffman, 4:21 (No. 4681—$1.00)

Forest Products Journal Index . . . 1972

Articles are listed in two ways: by subject and by author. The Subject Index is organized according to the four major FPRS Divisions — Products, Management, Processes, and Fundamental Disciplines. Under each Division heading, subject headings are listed in accordance with the FPRS Technical Committee structure. Articles are filed alphabetically under the appropriate subject heading(s).

The Author Index contains an entry for each author, with complete information listed under the senior author; listings for co-authors refer back to the senior author.

Reprints of all articles listed in the index may be obtained. The reprint order number and the cost per single copy are listed in both sections. Prices are based on 20 cents per printed page, with a $1.50 maximum charge per reprint. Special bulk rates are available. Check or money order must accompany all orders.

FPRS Subject Index . . . Vol. 22, 1972

PRODUCTS DIVISION

Softwood Lumber

Boring Deep Holes in Southern Pine, G. E. Woodson and C. W. McMillin, 4:49 (No. 4700—$1.00)

Can the Electrical Moisture Meter be Used for Testing Lumber to Meet American Lumber Standards? W. J. Delmhorst, 12:40 (No. 4732—$.60)

Drying Southern Pine at 240°F.—Effects of Air Velocity and Humidity, Board Thickness and Density, P. Koch, 9:62 (No. 4821—$1.20)

Dynamic Compression Results in Greatly Increased Creosote Retention in Spruce Heartwood, M. Y. Cech and D. R. Huffman, 4:21 (No. 4681—$1.00)

Effect of Single Knots on Tensile Strength of 2 by 8 Douglas-Fir Dimension Lumber, R. H. Kunesh and J. W. Johnson, 1:32 (No. 4649—$1.00)

Kiln- and Boulton-Drying Douglas-Fir Pole Sections at 220° to 290°F., R. D. Graham and R. J. Womack, 10:50 (No. 4806—$1.20)

Kiln Drying of Southern Pine Poles: Results of Laboratory and Field Studies, W. S. Thompson and R. R. Stevens, 3:17 (No. 4688—$1.50)

Moisture Content of Southern Pine as Related to Thrust, Torque, and Chip Formation in Boring, C. W. McMillin and G. E. Woodson, 11:55 (No. 4820—$1.00)

Nondestructive Parameters of Lodgepole Pine Dimension Lumber in Bending, M. R. O'Halloran, J. Bodig, and D. C. Bowden, 2:44 (No. 4654—$1.50)

Plasticizing Distortion-Prone Softwood Studs Prior to High Temperature Seasoning, J. F. G. Mackay and B. L. Rumball, 6:27 (No. 4711—$.40)

Predicting Moisture Content in Douglas-Fir and Ponderosa Pine Boards, D. P. Lowery, 12:35 (No. 4861—$1.00)

Reducing Variability in Final Moisture Content of Kiln-Dried Western Hemlock Lumber, C. J. Kozlik and L. W. Hamlin, 7:24 (No. 4781—$1.50)

Resistance Moisture Meter Correction Factors for Western Softwood Species, M. Salamon, 12:46 (No. 4847—$.40)

Steaming under Restraint to Remove Warp in Dried Softwood Studs, W. A. Dost and D. G. Arganbright, 3:42 (No. 4690—$.60)

Shear Strength of High-Temperature Heat-Treated Douglas-Fir Lumber Laminated with Phenol-Resorcinol Adhesives, J. D. Bohlen, 12:17 (No. 4822—$1.50)

Suitability of Commercial Hem-Fir for Preservative-Treated Lumber and Glued-Laminated Beams, G. Bramhall and P. A. Cooper, 2:33 (No. 4666—$1.00)

Hardwood Lumber

Azeotropic Drying of Yellow Birch and Hard Maple Lumber, D. R. Huffman, F. Pfaff, and S. M. Shah, 8:53 (No. 4757—$.80)

Drying of Predrilled Aspen Lumber, R. Erickson and L. Demaree, 11:48 (TN-230—$.60)

Germany's Parquet Flooring Industry—The Struggle to Survive, H. Kubler and J. Lempelius, 10:14 (No. 4929—$.60)

Kiln-Drying Aspen Studs, D. R. Huffman, 10:21 (TN-232—$.60)

Kiln-Drying of Presurfaced 4/4 Appalachian Oak, D. G. Cuppett and E. P. Craft, 6:36 (No. 4752—$1.20)

New Kiln Schedule for Presurfaced Oak Lumber, J. M. McMillen and R. C. Baltes, 5:19 (No. 4769—$1.50)

Sawing Method Effect on the Production of Cherry Lumber, P. C. Kersavage, 8:33 (No. 4780—$1.50)

Sawing Pattern and Bolt Quality Effects on Yield and Productivity from Yellow Birch, D. W. Bousquet, 11:39 (No. 4793—$1.50)

Sawing Pattern Effect on the Yield of Lumber and Furniture Components from Medium and Low Grade Hard Maple Logs, S. M. Pnevmaticos and D. W. Bousquet, 3:34 (No. 4652—$1.50)

Treated Wood Products

Changes in Creosote Content of Immersed Wood, D. J. Miller, 3:25 (No. 4621—$1.50)

Characteristics of Preservative Solutions which Influence their Penetration of Wood, D. D. Nicholas, 5:31 (No. 4730—$1.20)

Condition of Preservative-Treated Cooling Tower Slats After 10-Year Service, L. R. Gjovik, B. A. Bendtsen, and H. G. Roth, 4:35 (No. 4674—$1.20)

Development of an All-Weather, Fire-Retardant Treatment, B. H. Shunk, 2:12 (No. 4682—$.80)

Development of Respirometry as a Method for Evaluating Wood Preservatives, E. A. Behr, 4:26 (No. 4685—$1.20)

Discontinuous Treatment for Flame-Spread Control, W. T. Nearn and R. A. Megraw, 7:47 (No. 4735—$1.20)

Dynamic Compression Results in Greatly Increased Creosote Retention in Spruce Heartwood, M. Y. Cech and D. R. Huffman, 4:21 (No. 4681—$1.00)

Fire-Tube Tests of Wood-Polymer Composites, J. F. Siau, J. A. Meyer, and R. S. Kulik, 7:31 (No. 4758—$1.40)

Is Wood Hardness Affected by Preservative Treatment? R. L. Ethington, 5:60 (No. 4733—$.40)

Kiln- and Boulton-Drying Douglas-Fir Pole Sections at 220° to 290°F., R. D. Graham and R. J. Womack, 10:50 (No. 4806—$1.20)

Methods of Evaluating Fire-Retardant Treatments for Wood Shingles, C. A. Holmes, 3:45 (No. 4678—$1.20)

New Method for Making Particleboard Fire-Retardant, K. C. Shen and D. P. C. Fung, 8:46 (No. 4786—$1.40)

Paradichlorobenzene for Temporary Protection of Wood Against Fungi, T. C. Scheffer and R. D. Graham, 8:40 (No. 4800—$.40)

Penetrability and Strength of White Spruce after Ponding, H. H. Unligil, 9:92 (No. 4779—$1.50)

Pollution Control in the Wood-Preserving Industry. Part III: Chemical and Physical Methods of Treating Wastewater, J. V. Dust and W. S. Thompson, 12:25 (No. 4857—$1.20)

Pollution Control in the Wood-Preserving Industry. Part II. In-Plant Process Changes and Sanitation, W. S. Thompson and J. V. Dust, 7:42 (No. 4777—$1.20)

Retention of Creosote in Sapwood of Douglas-Fir, Ponderosa Pine, and Southern Pine Wafers Immersed in Water, D. J. Miller, 11:51 (No. 4812—$1.00)

Stable and Leach-Resistant Fire Retardants for Wood, S. C. Juneja, 6:17 (No. 4704—$1.40)

Suitability of Commercial Hem-Fir for Preservative-Treated Lumber and Glued-Laminated Beams, G. Bramhall and P. A. Cooper, 2:33 (No. 4666—$1.00)

Tolerance of Some Canadian Strains of Wood-Rotting Fungi to Wood Preservatives, H. H. Unligil, 1:40 (No. 4646—$1.20)

Vacuum-Pressure Impregnation of Medium-Density Hardboard with Phenolic Resin, W. S. McNamara and M. D. Shaw, 11:19 (No. 4844—$.80)

Weather-Ometer Studies on Wood-Plastic Composites, R. L. Desai, and S. C. Juneja, 9:100 (No. 4773—$.80)

Construction Plywood

Influence of Gluing Conditions on Performance of Crosslinked Protein Glue in Interior-Type Southern Pine Plywood, F. B. Weakley and C. L. Mehltretter, 1:45 (No. 4620—$1.20)

Irreversible Dimensional Changes in Panel Materials, B. G. Heebink, 5:44 (No. 4768—$1.00)

A Study on the Cause for Variation in Plywood Bond Quality with Open Assembly Time, G. E. Troughton and S.-Z. Chow, 3:55 (No. 4669—$.80)

Test for Measuring Formaldehyde Emission from Formaldehyde Resin Bonded Particleboards and Plywood, R. L. Christensen, 4:17 (No. 4734—$.80)

Wettability of Southern Pine Veneer by Phenol Formaldehyde Wood Adhesives, C.-Y. Hse, 1:51 (No. 4614—$1.20)

Decorative Veneers and Plywood

Irreversible Dimensional Changes in Panel Materials, B. G. Heebink, 5:44 (No. 4768—$1.00)

Modulus of Elasticity and Shear Deflection of Walnut-Veneered-Particleboard Composite Beams in Flexure, P. Chow, 11:33 (No. 4849—$1.20)

Particleboard and Molded Products

Decay and Termite Resistance of Medium-Density Fiberboards Made from Wood Residue, E. A. Behr, 12:48 (No. 4804—$.80)

Effect of Moisture on Physical Creep Properties of Particleboard, A. F. Halligan and A. P. Schniewind, 4:41 (No. 4696—$1.50)

Influence of the Amount and Type of Phenolic Resin on the Properties of a Wafer-Type Particleboard, J. G. Haygreen and R. O. Gertjejansen, 12:30 (No. 4855—$1.00)

Irreversible Dimensional Changes in Panel Materials, B. G. Heebink, 5:44 (No. 4768—$1.00)

Linear Hygroscopic Expansion of Selected Commercial Particleboards, O. Suchsland, 11:28 (No. 4825—$1.00)

Modulus of Elasticity and Shear Deflection of Walnut-Veneered-Particleboard Composite Beams in Flexure, P. Chow, 11:33 (No. 4849—$1.20)

Molding Characteristics of Some Mixtures of Douglas-Fir Bark and Phenolic Resin, D. J. Miller, 9:67 (TN-233—$.80)

Moisture-Stability Relationships in Wood-Base Composition Boards, W. F. Lehmann, 7:53 (No. 4785—$1.40)

New Environment in Particleboard Plants, T. M. Maloney, 6:11 (No. 4814—$.80)

New Method for Making Particleboard Fire-Retardant, K. C. Shen and D. P. C. Fung, 8:46 (No. 4786—$1.40)

Particleboard Blow Detector, A. S. Birks, 6:23 (No. 4705—$.80)

Test for Measuring Formaldehyde Emission from Formaldehyde Resin Bonded Particleboards and Plywood, R. L. Christensen, 4:17 (No. 4734—$.80)

Hardboard and Insulation Board

Irreversible Dimensional Changes in Panel Materials, B. G. Heebink, 5:44 (No. 4768—$1.00)

Methods for Measuring Die-Cutting Shear Strength of Hardboard, J. D. McNatt, 6:32 (No. 4701—$1.00)

Moisture Problems in Flush Garage Doors, R. C. Marck, 10:17 (No. 4834—$1.00)

Vacuum-Pressure Impregnation of Medium-Density Hardboard with Phenolic Resin, W. S. McNamara and M. D. Shaw, 11:19 (No. 4844—$.80)

Pulp and Paper

Study of Corrugated Board Cutting by High Velocity Liquid Jet, R. Szymani, 8:17 (No. 4697—$1.50)

Furniture, Dimension, and Turned Stock

Effects of Three Sawing Methods on Warp of Hard Maple Dimension Cuttings, F. B. Malcolm and H. Hallock, 4:57 (No. 4726—$.80)

Finger Joint Feasibility in Furniture Production, W. K. Murphey and L. E. Rishel, 2:30 (TN-223—$.60)

Logging Residue is a Source of Valuable Black Walnut Dimension, D. E. Dunmire, E. F. Landt, and R. E. Bodkin, 1:13 (No. 4723—$1.00)

Millwork, Cabinets, and Fixtures

Laminated Wood, Components, and Engineered Structures

Condition of Preservative-Treated Cooling Tower Slats After 10-Year Service, L. R. Gjovik, B. A. Bendtsen, and H. G. Roth, 4:35 (No. 4674—$1.20)

FPL Press-Lam Process: Fast, Efficient Conversion of Logs into Structural Products, FPL Press-Lam Research Team, 11:11 (No. 4945—$1.50)

LVL—Laminated-Veneer Lumber: Development and Economics, J. C. Bohlen, 1:18 (No. 4664—$1.50)

Proof Loading of Tension Laminations for Large Glued-Laminated Beams, R. F. Pellerin and M. D. Strickler, 10:24 (No. 4836—$1.40)

Shear Strength of High-Temperature Heat-Treated Douglas-Fir Lumber Laminated with Phenol-Resorcinol Adhesives, J. D. Bohlen, 12:17 (No. 4822—$1.50)

Stiffness-Graded Eastern Spruce Laminated Beams, E. N. Aplin, 1:26 (No. 4628—$1.20)

Suitability of Commercial Hem-Fir for Preservative-Treated Lumber and Glued-Laminated Beams, G. Bramhall and P. A. Cooper, 2:33 (No. 4666—$1.00)

Residential and Commercial Buildings

Development of an All-Weather, Fire-Retardant Treatment, B. H. Shunk, 2:12 (No. 4682—$.80)

Insuring Noise Control in Wood-Framed Buildings, J. B. Grantham and T. B. Heebink, 5:36 (No. 4715—$1.50)

Joist Deflections Simulated by a Computer Program, A. Sliker, 9:71 (TN-238—$.60)

Lateral Tests of Wood Roof Sections Sheathed with Decking, J. W. Johnson, 6:54 (TN-234—$.40)

Manufactured Housing Systems and Their Relation to the Use of Wood Products, J. Haygreen and K. Turkia, 8:13 (No. 4895—$.80)

Methods of Evaluating Fire-Retardant Treatments for Wood Shingles, C. A. Holmes, 3:45 (No. 4678—$1.20)

Moisture in Wood Structures for Ice Skating, A. E. Oviatt, 3:50 (No. 4677—$1.00)

Moisture Problems in Flush Garage Doors, R. C. Marck, 10:17 (No. 4834—$1.00)

New Consumer Profiles and the Changing Housing Market, S. U. Rich, 2:9 (No. 4770—$.80)

Predicting Damping in Wood Structures, Anonymous, 2:59 (TN-225—$.40)

Regulations Affecting Wood Use in Building Construction, M. Applefield, 2:12 (No. 4807—$1.00)

Response of Nailed Wood-Joist Floors to Static Loads, A. Polensek, G. H. Atherton, S. E. Corder, and J. L. Jenkins, 9:52 (No. 4851—$1.50)

Pallets and Containers

Four-Stringer Wood Pallets Save Dollars by Decreasing Buckling of Gallon Cans, L. W. Neubauer and Q. A. Hossain, 12:42 (No. 4867—$.80)

Tropical Woods

Void Volume Wood: An Any Tree-Whole Tree Use Concept, M. Chudnoff, 6:49 (No. 4743—$1.00)

Bark and Residues

A Study of Bark Removal at Low Temperatures by Simulated Cambium-Shear Methods, W. W. Calvert and A. M. Garlicki, 2:37 (No. 4653—$1.40)

Decay and Termite Resistance of Medium-Density Fiberboards Made from Wood Residue, E. A. Behr, 12:48 (No. 4804—$.80)

Effect of Sawdust Age and Nitrogen Application on Chrysanthemums Grown in White Oak Sawdust Media, S. Still, J. B. Gartner, and T. D. Hughes, 9:11 (No. 4810—$.80)

Hardwood-Bark-Sawdust Compost for Greenhouse Pot Flower Production, E. G. Scott and B. C. Bearse, 1:36 (No. 4641—$.80)

Lignin Utilization II—Resin Properties of 4-Alkyl Substituted Catechol Compounds, G. E. Troughton, J. F. Manville, and S.-Z. Chow, 9:108 (No. 4828—$.60)

Logging Residue is a Source of Valuable Black Walnut Dimension, D. E. Dunmire, E. F. Landt, and R. E. Bodkin, 1:13 (No. 4723—$1.00)

Molding Characteristics of Some Mixtures of Douglas-Fir Bark and Phenolic Resin, D. J. Miller, 9:67 (TN-233—$.80)

Segregation of Aspen, Balsam, and Spruce Wood and Bark Chips Based on Density Differences, L. M. Julien, J. C. Edgar, and T. M. Conder, 6:56 (No. 4687—$.80)

Separation of Wood and Bark by Gyratory Screening, J. M. Harkin and D. M. Crawford, 5:26 (TN-227—$1.00)

Some Physical Characteristics of Bark from Plantation-Grown Slash and Loblolly Pine, D. R. Phillips and J. G. Schroeder, 10:30 (No. 4856—$.80)

Treatment of Douglas-Fir Bark with Gaseous Ammonia, M. L. Laver, J. V. Zerrudo, and H. Aft, 9:82 (No. 4817—$1.40)

MANAGEMENT DIVISION

Production Management

A Semi-Automatic Veneer-Thickness Measuring System, R. S. Myronuk, 4:32 (TN-228—$.60)

Can the Electrical Moisture Meter be Used for Testing Lumber to Meet American Lumber Standards? W. J. Delmhorst, 12:40 (No. 4732—$.60)

Determining Maximum Stumpage Values for Wood Products Mills with Alternative Processes, G. R. Sampson, 8:26 (No. 4808—$1.00)

Dynamic Programming in Tree Bucking, S. Pnevmaticos and S. H. Mann, 2:26 (No. 4663—$1.00)

Evaluation of Microwave and Nuclear Moisture Gages for Establishing Water Content Segregations, E. O. Walters, 2:52 (No. 4449—$1.20)

FPL Press-Lam Process: Fast, Efficient Conversion of Logs into Structural Products, FPL Press-Lam Research Team, 11:11 (No. 4945—$1.50)

Joist Deflections Simulated by a Computer Program, A. Sliker, 9:71 (TN-238—$.60)

Matching of Chain Saw Power Requirements with Engine Characteristics, D. D. Reynolds and W. Soedel, 1:56 (No. 4613—$1.00)

Method to Analyze Rough Mill Productivity, R. M. Hallett, 11:22 (No. 4823—$1.20)

New Environment in Particleboard Plants, T. M. Maloney, 6:11 (No. 4814—$.80)

Particleboard Blow Detector, A. S. Birks, 6:23 (No. 4705—$.80)

Ratio-Delay—A Method for Analyzing Downtime in Sawmills, F. J. Hotemo and P. J. Dyson, 8:56 (No. 4767—$1.00)

Relevance of FPRS to the Small- and Medium-Size Wood Products Manufacturer, R. W. Wellwood, 9:40 (No. 4923—$.60)

Sawing Method Effect on the Production of Cherry Lumber, P. C. Kersavage, 8:33 (No. 4780—$1.50)

Sawing Pattern and Bolt Quality Effects on Yield and Productivity from Yellow Birch, D. W. Bousquet, 11:39 (No. 4793—$1.50)

Sawing Pattern Effect on the Yield of Lumber and Furniture Components from Medium and Low Grade Hard Maple Logs, S. M. Pnevmaticos and D. W. Bousquet, 3:34 (No. 4652—$1.50)

Sawmill Simulation Model for Maximizing Log Yield Values, L. K. Cummins and D. D. Culbertson, 10:34 (No. 4829—$1.40)

Void Volume Wood: An Any Tree-Whole Tree Use Concept, M. Chudnoff, 6:49 (No. 4743—$1.00)

Marketing

Manufactured Housing Systems and Their Relation to the Use of Wood Products, J. Haygreen and K. Turkia, 8:13 (No. 4895—$.80)

New Consumer Profiles and the Changing Housing Market, S. U. Rich, 2:9 (No. 4770—$.80)

Regulations Affecting Wood Use in Building Construction, M. Applefield, 2:12 (No. 4807—$1.00)

Economics and Financial Management

A New Approach for Projecting Long Term Timber Supply and Inventory, W. A. Leuschner, 5:49 (No. 4727—$1.00)

An Assessment of the Economic Benefits of Double-Cut Headrigs, J. Dobie and W. J. Sturgeon, 2:22 (No. 4667—$.60)

Four-Stringer Wood Pallets Save Dollars by Decreasing Buckling of Gallon Cans, L. W. Neubauer and Q. A. Hossain, 12:42 (No. 4867—$.80)

Germany's Parquet Flooring Industry—The Struggle to Survive, H. Kubler and J. Lempelius, 10:14 (No. 4929—$.60)

LVL—Laminated-Veneer Lumber: Development and Economics, J. C. Bohlen, 1:18 (No. 4664—$1.50)

Relevance of FPRS to the Small- and Medium-Size Wood Products Manufacturer, R. W. Wellwood, 9:40 (No. 4923—$.60)

Shift-Share Analysis of Southern Forest Industry, G. F. Dutrow, 12:10 (No. 4853—$1.20)

Southern Forestry Investments in an Era of Environmental Concern, W. C. Anderson, 6:14 (No. 4832—$.60)

Southern Timber Supply Trends and Outlook, H. S. Sternitzke and J. F. Christopher, 7:13 (No. 4846—$.80)

Research Management

Future of Wood as an Engineered Material, G. G. Marra, 9:43 (No. 4908— $1.50)

Role of Research in the Forest Products Industries, B. S. Bryant, 1:9 (No. 4792—$.80)

Quality Control

Measuring Screw Withdrawal with a Torque Wrench, M. N. Carroll, 8:42 (No. 4794—$1.00)

Prediction of Failure of Finger Joints Using Acoustic Emissions, A. W.

Porter, M. L. El-Osta, and D. J. Kusec, 9:74 (No. 4909—$1.50)

Weight as a Quality Control Factor in the Manufacture of Wood Ladder Rails, C. S. Walters, 8:30 (No. 4765—$.60)

PROCESSES DIVISION

Timber Production

A New Approach for Projecting Long Term Timber Supply and Inventory, W. A. Leuschner, 5:49 (No. 4727—$1.00)

Determining Maximum Stumpage Values for Wood Products Mills with Alternative Processes, G. R. Sampson, 8:26 (No. 4808—$1.00)

Dynamic Programming in Tree Bucking, S. Pnevmaticos and S. H. Mann, 2:26 (No. 4663—$1.00)

Heating Frozen and Nonfrozen Veneer Logs, O. Feihl, 10:41 (No. 4798—$1.50)

Matching of Chain Saw Power Requirements with Engine Characteristics, D. D. Reynolds and W. Soedel, 1:56 (No. 4613—$1.00)

Seasonal Moisture Content of Loblolly and Slash Pine, J. G. Schroeder and D. R. Phillips, 4:54 (No. 4713—$.60)

Southern Forestry Investments in an Era of Environmental Concern, W. C. Anderson, 6:14 (No. 4832—$.60)

Southern Timber Supply Trends and Outlook, H. S. Sternitzke and J. F. Christopher, 7:13 (No. 4846—$.80)

Drying and Storage

Azeotropic Drying of Yellow Birch and Hard Maple Lumber, D. R. Huffman, F. Pfaff, and S. M. Shah, 8:53 (No. 4757—$.80)

Can the Electrical Moisture Meter be Used for Testing Lumber to Meet American Lumber Standards? W. J. Delmhorst, 12:40 (No. 4732—$.60)

Drying of Predrilled Aspen Lumber, R. Erickson and L. Demaree, 11:48 (TN-230—$.60)

Drying Problems in the Pacific Northwest, C. J. Kozlik, 7:19 (No. 4818—$.20)

Drying Southern Pine at 240°F.—Effects of Air Velocity and Humidity, Board Thickness and Density, P. Koch, 9:62 (No. 4821—$1.20)

Effects of Three Sawing Methods on Warp of Hard Maple Dimension Cuttings, F. B. Malcolm and H. Hallock, 4:57 (No. 4726—$.80)

Evaluation of Microwave and Nuclear Moisture Gages for Establishing Water Content Segregations, E. O. Walters, 2:52 (No. 4449—$1.20)

Kiln- and Boulton-Drying Douglas-Fir Pole Sections at 220° to 290°F., R. D. Graham and R. J. Womack, 10:50 (No. 4806—$1.20)

Kiln-Drying Aspen Studs, D. R. Huffman, 10:21 (TN-232—$.60)

Kiln-Drying of Presurfaced 4/4 Appalachian Oak, D. G. Cuppett and E. P. Craft, 6:36 (No. 4752—$1.20)

Kiln-Drying of Southern Pine Poles: Results of Laboratory and Field Studies, W. S. Thompson and R. R. Stevens, 3:17 (No. 4688—$1.50)

New Kiln Schedule for Presurfaced Oak Lumber, J. M. McMillen and R. C. Baltes, 5:19 (No. 4769—$1.50)

Paradichlorobenzene for Temporary Protection of Wood Against Fungi, T. C. Scheffer and R. D. Graham, 8:40 (No. 4800—$.40)

Penetrability and Strength of White Spruce after Ponding, H. H. Unligil, 9:92 (No. 4779—$1.50)

Plasticizing Distortion-Prone Softwood Studs Prior to High Temperature Seasoning, J. F. G. Mackay and B. L. Rumball, 6:27 (No. 4711—$.40)

Predicting Moisture Content in Douglas-Fir and Ponderosa Pine Boards, D. P. Lowery, 12:35 (No. 4861—$1.00)

Resistance Moisture Meter Correction Factors for Western Softwood Species, M. Salamon, 12:46 (No. 4847—$.40)

Reducing Variability in Final Moisture Content of Kiln-Dried Western Hemlock Lumber, C. J. Kozlik and L. W. Hamlin, 7:24 (No. 4781—$1.50)

Regional Activities and Drying Problems in California, W. A. Dost, 7:23 (No. 4802—$.40)

Regional Activities and Drying Problems in the New England Kiln Drying Association Area, W. W. Rice, 7:20 (No. 4744—$.60)

Regional Activities and Drying Problems in the Wisconsin-Michigan Seasoning Association, C. W. Danielson, 7:17 (No. 4784—$.60)

Steaming under Restraint to Remove Warp in Dried Softwood Studs, W. A. Dost and D. G. Arganbright, 3:42 (No. 4690—$.60)

Wood Drying Review—1970, E. D. Sprague, 2:17 (No. 4670—$1.00)

Gluing

A Study on the Cause for Variation in Plywood Bond Quality with Open Assembly Time, G. E. Troughton and S.-Z. Chow, 3:55 (No. 4669—$.80)

Finger Joint Feasibility in Furniture Production, W. K. Murphey and L. E. Rishel, 2:30 (TN-223—$.60)

Influence of Gluing Conditions on Performance of Crosslinked Protein Glue in Interior-Type Southern Pine Plywood, F. B. Weakley and C. L. Mehltretter, 1:45 (No. 4620—$1.20)

Influence of Resin Formulation Variables on Bond Quality of Southern Pine Plywood, C.-Y. Hse, 9:104 (No. 4787—$1.00)

Influence of the Amount and Type of Phenolic Resin on the Properties of a Wafer-Type Particleboard, J. G. Haygreen and R. O. Gertjejansen, 12:30 (No. 4855—$1.00)

Lignin Utilization II—Resin Properties of 4-Alkyl Substituted Catechol Compounds, G. E. Troughton, J. F. Manville, and S.-Z. Chow, 9:108 (No. 4828—$.60)

Prediction of Failure of Finger Joints Using Acoustic Emissions, A. W. Porter, M. L. El-Osta, and D. J. Kusec, 9:74 (No. 4909—$1.50)

Shear Strength of High-Temperature Heat-Treated Douglas-Fir Lumber Laminated with Phenol-Resorcinol Adhesives, J. D. Bohlen, 12:17 (No. 4822—$1.50)

Suitability of Commercial Hem-Fir for Preservative-Treated Lumber and Glued-Laminated Beams, G. Bramhall and P. A. Cooper, 2:33 (No. 4666—$1.00)

Test for Measuring Formaldehyde Emission from Formaldehyde Resin Bonded Particleboards and Plywood, R. L. Christensen, 4:17 (No. 4734—$.80)

Wettability of Southern Pine Veneer by Phenol Formaldehyde Wood Adhesives, C.-Y. Hse, 1:51 (No. 4614—$1.20)

Mechanical Fastening

Measuring Screw Withdrawal with a Torque Wrench, M. N. Carroll, 8:42 (No. 4794—$1.00)

Milling and Machining

A Semi-Automatic Veneer-Thickness Measuring System, R. S. Myronuk, 4:32 (TN-228—$.60)

A Study of Bark Removal at Low Temperatures by Simulated Cambium-Shear Methods, W. W. Calvert and A. M. Garlicki, 2:37 (No. 4653—$1.40)

An Assessment of the Economic Benefits of Double-Cut Headrigs, J. Dobie and W. J. Sturgeon, 2:22 (No. 4667—$.60)

An Instrument for Measuring Knife Height on Veneer Lathes, D. C. Walser, 3:59 (TN-226—$.40)

Boring Deep Holes in Southern Pine, G. E. Woodson and C. W. McMillin, 4:49 (No. 4700—$1.00)

Boring 40-Foot Long Utility Poles for Conduit Passage, M. H. Mater, 6:28 (No. 4706—$.80)

Effects of Three Sawing Methods on Warp of Hard Maple Dimension Cuttings, F. B. Malcolm and H. Hallock, 4:57 (No. 4726—$.80)

Finger Joint Feasibility in Furniture Production, W. K. Murphey and L. E. Rishel, 2:30 (TN-223—$.60)

LVL—Laminated-Veneer Lumber: Development and Economics, J. C. Bohlen, 1:18 (No. 4664—$1.50)

Matching of Chain Saw Power Requirements with Engine Characteristics, D. D. Reynolds and W. Soedel, 1:56 (No. 4613—$1.00)

Method to Analyze Rough Mill Productivity, R. M. Hallett, 11:22 (No. 4823—$1.20)

Methods for Measuring Die-Cutting Shear Strength of Hardboard, J. D. McNatt, 6:32 (No. 4701—$1.00)

Moisture Content of Southern Pine as Related to Thrust, Torque, and Chip Formation in Boring, C. W. McMillin and G. E. Woodson, 11:55 (No. 4820—$1.00)

Ratio-Delay—A Method for Analyzing Downtime in Sawmills, F. J. Holemo and P. J. Dyson, 8:56 (No. 4767—$1.00)

Sawing Method Effect on the Production of Cherry Lumber, P. C. Kersavage, 8:33 (No. 4780—$1.50)

Sawing Pattern and Bolt Quality Effects on Yield and Productivity from Yellow Birch, D. W. Bousquet, 11:39 (No. 4793—$1.50)

Sawing Pattern Effect on the Yield of Lumber and Furniture Components from Medium and Low Grade Hard Maple Logs, S. M. Pnevmaticos and D. W. Bousquet, 3:34 (No. 4652—$1.50)

Sawmill Simulation Model for Maximizing Log Yield Values, L. K. Cummins and D. D. Culbertson, 10:34 (No. 4829—$1.40)

Recent Developments in Circular Rip Sawing, T. A. McLauchlan, 6:42 (No. 4709—$1.40)

Study of Corrugated Board Cutting by High Velocity Liquid Jet, R. Szymani, 8:17 (No. 4697—$1.50)

Thick Slicing of Wood: Effects of Wood and Knife Inclination Angle, C. C. Peters, A. F. Mergen, and H. R. Panser, 9:84 (No. 4738—$1.50)

Finishing and Overlaying

Pollution Abatement and Control

Insuring Noise Control in Wood-Framed Buildings, J. B. Grantham and T. B. Heebink, 5:36 (No. 4715—$1.50)

New Environment in Particleboard Plants, T. M. Maloney, 6:11 (No. 4814—$.80)

Pollution Control in the Wood-Preserving Industry. Part III: Chemical and Physical Methods of Treating Wastewater, J. V. Dust and W. S. Thompson, 12:25 (No. 4857—$1.20)

Pollution Control in the Wood-Preserving Industry. Part II. In-Plant Process Changes and Sanitation, W. S. Thompson and J. V. Dust, 7:42 (No. 4777—$1.20)

Test for Measuring Formaldehyde Emission from Formaldehyde Resin Bonded Particleboards and Plywood, R. L. Christensen, 4:17 (No. 4734—$.80)

FUNDAMENTAL DISCIPLINES DIVISION

Biology

Decay and Termite Resistance of Medium-Density Fiberboards Made from Wood Residue, E. A. Behr, 12:48 (No. 4804—$.80)

Development of Respirometry as a Method for Evaluating Wood Preservatives, E. A. Behr, 4:26 (No. 4685—$1.20)

Penetrability and Strength of White Spruce after Ponding, H. H. Unligil, 9:92 (No. 4779—$1.50)

Relationships of Specific Gravity to Tree Height in Commercially Important Species, E. A. Okkonen, H. E. Wahlgren, and R. R. Maeglin, 7:37 (No. 4753—$1.20)

Seasonal Moisture Content of Loblolly and Slash Pine, J. G. Schroeder and D. R. Phillips, 4:54 (No. 4713—$.60)

Some Physical Characteristics of Bark from Plantation-Grown Slash and Loblolly Pine, D. R. Phillips and J. G. Schroeder, 10:30 (No. 4856—$.80)

Tolerance of Some Canadian Strains of Wood-Rotting Fungi to Wood Preservatives, H. H. Unligil, 1:40 (No. 4646—$1.20)

Wood Specific Gravity of Eleven Species of Pines, J. R. Saucier, 3:32 (TN-229—$.40)

Chemistry

Fire-Tube Tests of Wood-Polymer Composites, J. F. Siau, J. A. Meyer, and R. S. Kulik, 7:31 (No. 4758—$1.40)

Lignin Utilization II—Resin Properties of 4-Alkyl Substituted Catechol Compounds, G. E. Troughton, J. F. Manville, and S.-Z. Chow, 9:108 (No. 4828—$.60)

Pollution Control in the Wood-Preserving Industry. Part III: Chemical and Physical Methods of Treating Wastewater, J. V. Dust and W. S. Thompson, 12:25 (No. 4857—$1.20)

Weather-Ometer Studies on Wood-Plastic Composites, R. L. Desai, and S. C. Juneja, 9:100 (No. 4773—$.80)

Physics

Characteristics of Preservative Solutions which Influence their Penetration of Wood, D. D. Nicholas, 5:31 (No. 4730—$1.20)

Development of an All-Weather, Fire-Retardant Treatment, B. H. Shunk, 2:12 (No. 4682—$.80)

Discontinuous Treatment for Flame-Spread Control, W. T. Nearn and R. A. Megraw, 7:47 (No. 4735—$1.20)

Effect of Unidirectional Diffusion and Prefreezing upon Flexural Creep in Redwood, R. Erickson, M. M. Chen, and T. Lehtinen, 10:56 (No. 4658—$1.00)

Evaluation of Microwave and Nuclear Moisture Gages for Establishing Water Content Segregations, E. O. Walters, 2:52 (No. 4449—$1.20)

Fire-Tube Tests of Wood-Polymer Composites, J. F. Siau, J. A. Meyer, and R. S. Kulik, 7:31 (No. 4758—$1.40)

Heating Frozen and Nonfrozen Veneer Logs, O. Feihl, 10:41 (No. 4798—$1.50)

Insuring Noise Control in Wood-Framed Buildings, J. B. Grantham and T. B. Heebink, 5:36 (No. 4715—$1.50)

Irreversible Dimensional Changes in Panel Materials, B. G. Heebink, 5:44 (No. 4768—$1.00)

Linear Hygroscopic Expansion of Selected Commercial Particleboards, O. Suchsland, 11:28 (No. 4825—$1.00)

Methods of Evaluating Fire-Retardant Treatments for Wood Shingles, C. A. Holmes, 3:45 (No. 4678—$1.20)

Moisture in Wood Structures for Ice Skating, A. E. Oviatt, 3:50 (No. 4677—$1.00)

Moisture-Stability Relationships in Wood-Base Composition Boards, W. F. Lehmann, 7:53 (No. 4785—$1.40)

Plasticizing Distortion-Prone Softwood Studs Prior to High Temperature Seasoning, J. F. G. Mackay and B. L. Rumball, 6:27 (No. 4711—$.40)

Predicting Moisture Content in Douglas-Fir and Ponderosa Pine Boards, D. P. Lowery, 12:35 (No. 4861—$1.00)

Prediction of Failure of Finger Joints Using Acoustic Emissions, A. W. Porter, M. L. El-Osta, and D. J. Kusec, 9:74 (No. 4909—$1.50)

Prefreezing Effects on Three Hardwoods, G. A. Cooper and S. H. Barham, 2:24 (No. 4637—$.40)

Prefreezing Reduces Shrinkage and Alters Sorption in Black Walnut, G. A. Cooper, 5:54 (No. 4665—$1.40)

Wettability of Southern Pine Veneer by Phenol Formaldehyde Wood Adhesives, C.-Y. Hse, 1:51 (No. 4614—$1.20)

Wood Engineering and Mechanical Properties

Dynamic Compression Results in Greatly Increased Creosote Retention in Spruce Heartwood, M. Y. Cech and D. R. Huffman, 4:21 (No. 4681—$1.00)

Effect of Moisture on Physical Creep Properties of Particleboard, A. F. Halligan and A. P. Schniewind, 4:41 (No. 4696—$1.50)

Effect of Single Knots on Tensile Strength of 2 by 8 Douglas-Fir Dimension Lumber, R. H. Kunesh and J. W. Johnson, 1:32 (No. 4649—$1.00)

Effect of Unidirectional Diffusion and Prefreezing upon Flexural Creep in Redwood, R. Erickson, M. M. Chen, and T. Lehtinen, 10:56 (No. 4658—$1.00)

Future of Wood as an Engineered Material, G. G. Marra, 9:43 (No. 4908—$1.50)

Is Wood Hardness Affected by Preservative Treatment? R. L. Ethington, 5:60 (No. 4733—$.40)

Joist Deflections Simulated by a Computer Program, A. Sliker, 9:71 (TN-238—$.60)

Lateral Tests of Wood Roof Sections Sheathed with Decking, J. W. Johnson, 6:54 (TN-234—$.40)

Measuring Screw Withdrawal with a Torque Wrench, M. N. Carroll, 8:42 (No. 4794—$1.00)

Methods for Measuring Die-Cutting Shear Strength of Hardboard, J. D. McNatt, 6:32 (No. 4701—$1.00)

Modulus of Elasticity and Shear Deflection of Walnut-Veneered-Particleboard Composite Beams in Flexure, P. Chow, 11:33 (No. 4849—$1.20)

Moisture Problems in Flush Garage Doors, R. C. Marck, 10:17 (No. 4834—$1.00)

Nondestructive Parameters of Lodgepole Pine Dimension Lumber in Bending, M. R. O'Halloran, J. Bodig, and D. C. Bowden, 2:44 (No. 4654—$1.50)
Penetrability and Strength of White Spruce after Ponding, H. H. Unligil, 9:92 (No. 4779—$1.50)
Predicting Damping in Wood Structures, Anonymous, 2:59 (TN-225—$.40)
Prediction of Failure of Finger Joints Using Acoustic Emissions, A. W. Porter, M. L. El-Osta, and D. J. Kusec, 9:74 (No. 4909—$1.50)
Prefreezing Reduces Shrinkage and Alters Sorption in Black Walnut, G. A. Cooper, 5:54 (No. 4665—$1.40)
Prefreezing Effects on Three Hardwoods, G. A. Cooper and S. H. Barham, 2:24 (No. 4637—$.40)
Proof Loading of Tension Laminations for Large Glued-Laminated Beams, R. F. Pellerin and M. D. Strickler, 10:24 (No. 4836—$1.40)
Relationships of Specific Gravity to Tree Height in Commercially Important Species, E. A. Okkonen, H. E. Wahlgren, and R. R. Maeglin, 7:37 (No. 4753—$1.20)
Response of Nailed Wood-Joist Floors to Static Loads, A. Polensek, G. H. Atherton, S. E. Corder, and J. L. Jenkins, 9:52 (No. 4851—$1.50)
Shear Strength of High-Temperature Heat-Treated Douglas-Fir Lumber Laminated with Phenol-Resorcinol Adhesives, J. D. Bohlen, 12:17 (No. 4822—$1.40)
Stiffness-Graded Eastern Spruce Laminated Beams, E. N. Aplin, 1:26 (No. 4628—$1.20)
Thick Slicing of Wood: Effects of Wood and Knife Inclination Angle, C. C. Peters, A. F. Mergen, and H. R. Panser, 9:84 (No. 4738—$1.50)
Void Volume Wood: An Any Tree-Whole Tree Use Concept, M. Chudnoff, 6:49 (No. 4743—$1.00)
Weather-Ometer Studies on Wood-Plastic Composites, R. L. Desai and S. C. Juneja, 9:100 (No. 4773—$.80)
Wood Specific Gravity of Eleven Species of Pines, J. R. Saucier, 3:32 (TN-229—$.40)

FPRS Author Index . . . Vol. 22, 1972

A

Aft, H., *see* Laver, M. L.
Anderson, W. C., Southern Forestry Investments in an Era of Environmental Concern, 6:14 (No. 4832—$.60)
Anonymous, Predicting Damping in Wood Structures, 2:59 (TN-225—$.40)
Aplin, E. N., Stiffness-Graded Eastern Spruce Laminated Beams, 1:26 (No. 4628—$1.20)
Applefield, M. Regulations Affecting Wood Use in Building Construction, 2:12 (No. 4807—$1.00)
Arganbright, D. G., *see* Dost, W. A.
Atherton, G. H., *see* Polensek, A.

B

Baltes, R. C., *see* McMillen, J. M.
Barham, S. H., *see* Cooper, G. A.
Bearse, B. C., *see* Scott, E. G.
Behr, E. A., Decay and Termite Resistance of Medium-Density Fiberboards Made from Wood Residue, 12:48 (No. 4804—$.80)
Behr, E. A., Development of Respirometry as a Method for Evaluating Wood Preservatives, 4:26 (No. 4685—$1.20)
Bendtsen, B. A., *see* Gjovik, L. R.
Birks, A. S., Particleboard Blow Detector, 6:23 (No. 4705—$.80)
Bodig, J., *see* O'Halloran, M. R.
Bodkin, R. E., *see* Dunmire, D. E.
Bohlen, J. C., LVL—Laminated-Veneer Lumber: Development and Economics, 1:18 (No. 4664—$1.50)
Bohlen, J. D., Shear Strength of High-Temperature Heat-Treated Douglas-Fir Lumber Laminated with Phenol-Resorcinol Adhesives, 12:17 (No. 4822—$1.50)
Bousquet, D. W., *see* Pnevmaticos, S. M.
Bousquet, D. W., Sawing Pattern and Bolt Quality Effects on Yield and Productivity from Yellow Birch, 11:39 (No. 4793—$1.50)
Bowden, D. C., *see* O'Halloran, M. R.
Bramhall, G., and P. A. Cooper, Suitability of Commercial Hem-Fir for Preservative-Treated Lumber and Glued-Laminated Beams, 2:33 (No. 4666—$1.00)
Bryant, B. S., Role of Research in the Forest Products Industries, 1:9 (No. 4792—$.80)

C

Calvert, W. W., and A. M. Garlicki, A Study of Bark Removal at Low Temperatures by Simulated Cambium-Shear Methods, 2:37 (No. 4653—$1.40)
Carroll, M. N., Measuring Screw Withdrawal with a Torque Wrench, 8:42 (No. 4794—$1.00)
Cech, M. Y., and D. R. Huffman, Dynamic Compression Results in Greatly Increased Creosote Retention in Spruce Heartwood, 4:21 (No. 4681—$1.00)
Chen, M. M., *see* Erickson, R.
Chow, P., Modulus of Elasticity and Shear Deflection of Walnut-Veneered-Particleboard Composite Beams in Flexure, 11:33 (No. 4849—$1.20)
Chow, S.-Z., *see* Troughton, G. E.
Christensen, R. L., Test for Measuring Formaldehyde Emission from Formaldehyde Resin Bonded Particleboards and Plywood, 4:17 (No. 4734—$.80)
Christopher, J. F. *see* Sternitzke, H. S.
Chudnoff, M., Void Volume Wood: An Any Tree-Whole Tree Use Concept, 6:49 (No. 4743—$1.00)
Conder, T. M., *see* Julien, L. M.
Cooper, G. A., Prefreezing Reduces Shrinkage and Alters Sorption in Black Walnut, 5:54 (No. 4665—$1.40)
Cooper, G. A., and S. H. Barham, Prefreezing Effects on Three Hardwoods, 2:24 (No. 4637—$.40)
Cooper, P. A., *see* Bramhall, G.
Corder, S. E., *see* Polensek, A.
Craft, E. P., *see* Cuppett, D. G.
Crawford, D. M., *see* Harkin, J. M.
Culbertson, D. D., *see* Cummins, L. K.
Cummins, L. K., and D. D. Culbertson, Sawmill Simulation Model for Maximizing Log Yield Values, 10:34 (No. 4829—$1.40)
Cuppett, D. G., and E. P. Craft, Kiln-Drying of Presurfaced 4/4 Appalachian Oak, 6:36 (No. 4752—$1.20)

D

Danielson, C. W., Regional Activities and Drying Problems in the Wisconsin-Michigan Seasoning Association Area, 7:17 (No. 4784—$.60)
Delmhorst, W. J., Can the Electrical Moisture Meter be Used for Testing Lumber to Meet American Lumber Standards? 12:40 (No. 4732—$.60)
Demaree, L., *see* Erickson, R.
Desai, R. L., and S. C. Juneja, Weather-Ometer Studies on Wood-Plastic Composites, 9:100 (No. 4773—$.80)
Dobie, J., and W. J. Sturgeon, An Assessment of the Economic Benefits of Double-Cut Headrigs, 2:22 (No. 4667—$.60)
Dost, W. A., Regional Activities and Drying Problems in California, 7:23 (No. 4802—$.40)
Dost, W. A., and D. G. Arganbright, Steaming under Restraint to Remove Warp in Dried Softwood Studs, 3:42 (No. 4690—$.60)
Dunmire, D. E., E. F. Landt, and R. E. Bodkin, Logging Residue is a Source

of Valuable Black Walnut Dimension, 1:13 (No. 4723—$1.00)
Dust, J. V., *see* Thompson, W. S.
Dust, J. V., and W. S. Thompson, Pollution Control in the Wood-Preserving Industry. Part III: Chemical and Physical Methods of Treating Wastewater, 12:25 (No. 4857—$1.20)
Dutrow, G. F., Shift-Share Analysis of Southern Forest Industry, 12:10 (No. 4853—$1.20)
Dyson, P. J., *see* Holemo, F. J.

E

Edgar, J. C., *see* Julien, L. M.
Erickson, R., M. M. Chen, and T. Lehtinen, The Effect of Unidirectional Diffusion and Prefreezing upon Flexural Creep in Redwood, 10:56 (No. 4658—$1.00)
Erickson, R., and L. Demaree, The drying of Predrilled Aspen Lumber, 11:48 (TN-230—$.60)
Ethington, R. L., Is Wood Hardness Affected by Preservative Treatment? 5:60 (No. 4733—$.40)

F

Feihl, O., Heating Frozen and Nonfrozen Veneer Logs, 10:41 (No. 4798—$1.50)
FPL Press-Lam Research Team, FPL Press-Lam Process: Fast, Efficient Conversion of Logs into Structural Products, 11:11 (No. 4945—$1.50)
Fung, D. P. C., *see* Shen, K. C.

G

Garlicki, A. M., *see* Calvert, W. W.
Gartner, J. B. *see* Still, S.
Gertjejansen, R. O., *see* Haygreen, J. G.
Graham, R. D., *see* Scheffer, T. C.
Graham, R. D., and R. J. Womack, Kiln- and Boulton-Drying Douglas-Fir Pole Sections at 220° to 290°F., 10:50 (No. 4806—$1.20)
Grantham, J. B., and T. B. Heebink, Insuring Noise Control in Wood-Framed Buildings, 5:36 (No. 4715—$1.50)
Gjovik, L. R., B. A. Bendtsen, and H. G. Roth, Condition of Preservative-Treated Cooling Tower Slats After 10-Year Service, 4:35 (No. 4674—$1.20)

H

Hallett, R. M., A Method to Analyze Rough Mill Productivity, 11:22 (No. 4823—$1.20)
Halligan, A. F., and A. P. Schniewind, Effect of Moisture on Physical Creep Properties of Particleboard, 4:41 (No. 4696—$1.50)
Hallock, H., *see* Malcolm, F. B.
Hamlin, L. W., *see* Kozlik, C. J.
Harkin, J. M., and D. M. Crawford, Separation of Wood and Bark by Gyratory Screening, 5:26 (TN-227—$1.00)
Haygreen, J. G., and R. O. Gertjejansen, Influence of the Amount and Type of Phenolic Resin on the Properties of a Wafer-Type Particleboard, 12:30 (No. 4855—$1.00)
Haygreen, J., and K. Turkia, Manufactured Housing Systems and Their Relation to the Use of Wood Products, 8:13 (No. 4895—$.80)
Heebink, B. G., Irreversible Dimensional Changes in Panel Materials, 5:44 (No. 4768—$1.00)
Heebink, T. B., *see* Grantham, J. B.
Holemo, F. J., and P. J. Dyson, Ratio-Delay—A Method for Analyzing Downtime in Sawmills, 8:56 (No. 4767—$1.00)
Holmes, C. A., Methods of Evaluating Fire-Retardant Treatments for Wood Shingles, 3:45 (No. 4678—$1.20)
Hossain, Q. A., *see* Neubauer, L. W.
Hse, C.-Y., Influence of Resin Formulation Variables on Bond Quality of Southern Pine Plywood, 9:104 (No. 4787—$1.00)
Hse, C.-Y., Wettability of Southern Pine Veneer by Phenol Formaldehyde Wood Adhesives, 1:51 (No. 4614—$1.20)
Huffman, D. R., *see* Cech, M. Y.
Huffman, D. R., Kiln-Drying Aspen Studs, 10:21 (TN-232—$.60)
Huffman, D. R., F. Pfaff, and S. M. Shah, Azeotropic Drying of Yellow Birch and Hard Maple Lumber, 8:53 (No. 4757—$.80)
Hughes, T. D., *see* Still, S.

J

Jenkins, J. L., *see* Polensek, A.
Johnson, J. W., *see* Kunesh, R. H.
Johnson, J. W., Lateral Tests of Wood Roof Sections Sheathed with Decking, 6:54 (TN-234—$.40)
Julien, L. M., J. C. Edgar, and T. M. Conder, Segregation of Aspen, Balsam, and Spruce Wood and Bark Chips Based on Density Differences, 6:56 (No. 4687—$.80)
Juneja, S. C., *see* Desai, R. L.
Juneja, S. C., Stable and Leach-Resistant Fire Retardants for Wood, 6:17 (No. 4704—$1.40)

K

Kersavage, P. C., Sawing Method Effect on the Production of Cherry Lumber, 8:33 (No. 4780—$1.50)
Koch, P., Drying Southern Pine at 240°F.—Effects of Air Velocity and Humidity, Board Thickness and Density, 9:62 (No. 4821—$1.20)
Kozlik, C. J., Drying Problems in the Pacific Northwest, 7:19 (No. 4818—$.20)
Kozlik, C. J., and L. W. Hamlin, Reducing Variability in Final Moisture Content of Kiln-Dried Western Hemlock Lumber, 7:24 (No. 4781—$1.50)
Kubler, H. and J. Lempelius, Germany's Parquet Flooring Industry—The Struggle to Survive, 10:14 (No. 4929—$.60)
Kulik, R. S., *see* Siau, J. F.
Kunesh, R. H., and J. W. Johnson, Effect of Single Knots on Tensile Strength of 2 by 8 Douglas-Fir Dimension Lumber, 1:32 (No. 4649—$1.00)

L

Landt, E. F., *see* Dunmire, D. E.
Laver, M. L., J. V. Zerrudo, and H. Aft, Treatment of Douglas-Fir Bark with Gaseous Ammonia, 9:82 (No. 4817—$1.40)
Lehmann, W. F., Moisture-Stability Relationships in Wood-Base Composition Boards, 7:53 (No. 4785—$1.40)
Lehtinen, T., *see* Erickson, R.
Lempelius, J., *see* Kubler, H.
Leuschner, W. A., A New Approach for Projecting Long Term Timber Supply and Inventory, 5:49 (No. 4727—$1.00)
Lowery, D. P., Predicting Moisture Content in Douglas-Fir and Ponderosa Pine Boards, 12:35 (No. 4861—$1.00)

M

Mackay, J. F. G., and B. L. Rumball, Plasticizing Distortion-Prone Softwood Studs Prior to High Temperature Seasoning, 6:27 (No. 4711—$.40)
Maeglin, R. R., *see* Okkonen, E. A.
Malcolm, F. B., and H. Hallock, Effects of Three Sawing Methods on Warp of Hard Maple Dimension Cuttings, 4:57 (No. 4726—$.80)
Maloney, T. M., The New Environment in Particleboard Plants, 6:11 (No. 4814—$.80)
Mann, S. H., *see* Pnevmaticos, S.
Manville, J. F., *see* Troughton, G. E.
Marck, R. C., Moisture Problems in Flush Garage Doors, 10:17 (No. 4834—$1.00)
Marra, G. G., The Future of Wood as an Engineered Material, 9:43 (No. 4908—$1.50)
Mater, M. H., Boring 40-Foot Long Utility Poles for Conduit Passage, 6:28 (No. 4706—$.80)
McLauchlan, T. A., Recent Developments in Circular Rip Sawing, 6:42 (No. 4709—$1.40)
McMillen, J. M., and R. C. Baltes, New Kiln Schedule for Presurfaced Oak Lumber, 5:19 (No. 4769—$1.50)
McMillin, C. W., *see* Woodson, G. E.
McMillin, C. W., and G. E. Woodson, Moisture Content of Southern Pine as Related to Thrust, Torque, and Chip Formation in Boring, 11:55 (No. 4820—$1.00)
McNamara, W. S., and M. D. Shaw, Vacuum-Pressure Impregnation of Medium-Density Hardboard with Phenolic Resin, 11:19 (No. 4844—$.80)
McNatt, J. D., Methods for Measuring Die-Cutting Shear Strength of Hardboard, 6:32 (No. 4701—$1.00)
Megraw, R. A., *see* Nearn, W. T.
Mehltretter, C. L., *see* Weakley, F. B.
Mergen, A. F., *see* Peters, C. C.
Meyer, J. A., *see* Siau, J. F.
Miller, D. J., Changes in Creosote Content of Immersed Wood, 3:25 (No. 4621—$1.50)

Miller, D. J., Molding Characteristics of Some Mixtures of Douglas-Fir Bark and Phenolic Resin, 9:67 (TN-233—$.80)
Miller, D. J., Retention of Creosote in Sapwood of Douglas-Fir, Ponderosa Pine, and Southern Pine Wafers Immersed in Water, 11:15 (No. 4812—$1.00)
Murphey, W. K., and L. E. Rishel, Finger Joint Feasibility in Furniture Production, 2:30 (TN-223—$.60)
Myronuk, R. S., A Semi-Automatic Veneer-Thickness Measuring System, 4:32 (TN-228—$.60)

N

Nearn, W. T., and R. A. Megraw, Discontinuous Treatment for Flame-Spread Control, 7:47 (No. 4735—$1.20)
Neubauer, L. W., and Q. A. Hossain, Four-Stringer Wood Pallets Save Dollars by Decreasing Buckling of Gallon Cans, 12:42 (No. 4867—$.80)
Nicholas, D. D., Characteristics of Preservative Solutions which Influence their Penetration of Wood, 5:31 (No. 4730—$1.20)

O

O'Halloran, M. R., J. Bodig, and D. C. Bowden, Nondestructive Parameters of Lodgepole Pine Dimension Lumber in Bending, 2:44 (No. 4654—$1.50)
Okkonen, E. A., H. E. Wahlgren, and R. R. Maeglin, Relationships of Specific Gravity to Tree Height in Commercially Important Species, 7:37 (No. 4753—$1.20)
Oviatt, A. E., Moisture in Wood Structures for Ice Skating, 3:50 (No. 4677—$1.00)

P

Panser, H. R., *see* Peters, C. C.
Pellerin, R. F., and M. D. Strickler, Proof Loading of Tension Laminations for Large Glued-Laminated Beams, 10:24 (No. 4836—$1.40)
Peters, C. C., A. F. Mergen, and H. R. Panser, Thick Slicing of Wood: Effects of Wood and Knife Inclination Angle, 9:84 (No. 4738—$1.50)
Pfaff, F., *see* Huffman, D. R.
Phillips, D. R., *see* Schroeder, J. G.
Phillips, D. R., and J. G. Schroeder, Some Physical Characteristics of Bark from Plantation-Grown Slash and Loblolly Pine, 10:30 (No. 4856—$.80)
Polensek, A., G. H. Atherton, S. E. Corder, and J. L. Jenkins, Response of Nailed Wood-Joist Floors to Static Loads, 9:52 (No. 4851—$1.50)
Pnevmaticos, S., and S. H. Mann, Dynamic Programming in Tree Bucking, 2:26 (No. 4663—$1.00)
Pnevmaticos, S. M., and D. W. Bousquet, Sawing Pattern Effect on the Yield of Lumber and Furniture Components from Medium and Low Grade Hard Maple Logs, 3:34 (No. 4652—$1.50)
Porter, A. W., M. L. El-Osta, and D. J. Kusec, Prediction of Failure of Finger Joints Using Acoustic Emissions, 9:74 (No. 4909—$1.50)

R

Reynolds, D. D., and W. Soedel, Matching of Chain Saw Power Requirements with Engine Characteristics, 1:56 (No. 4613—$1.00)
Rice, W. W., Regional Activities and Drying Problems in the New England Kiln Drying Association Area, 7:20 (No. 4744—$.60)
Rich, S. U., New Consumer Profiles and the Changing Housing Market, 2:9 (No. 4770—$.80)
Rishel, L. E., *see* Murphey, W. K.
Roth, H. G., *see* Gjovik, L. R.
Rumball, B. L., *see* Mackay, J. F. G.

S

Salamon, M., Resistance Moisture Meter Correction Factors for Western Softwood Species, 12:46 (No. 4847—$.40)
Sampson, G. R., Determining Maximum Stumpage Values for Wood Products Mills with Alternative Processes, 8:26 (No. 4808—$1.00)
Saucier, J. R., Wood Specific Gravity of Eleven Species of Pines, 3:32 (TN-229—$.40)
Scheffer, T. C., and R. D. Graham, Paradichlorobenzene for Temporary Protection of Wood Against Fungi, 8:40 (No. 4800—$.40)
Schniewind, A. P., *see* Halligan, A. F.
Schroeder, J. G. *see* Phillips, D. R.
Schroeder, J. G., and D. R. Phillips, Seasonal Moisture Content of Loblolly and Slash Pine, 4:54 (No. 4713—$.60)
Scott, E. G., and B. C. Bearse, Hardwood-Bark-Sawdust Compost for Greenhouse Pot Flower Production, 1:36 (No. 4641—$.80)
Shah, S. M., *see* Huffman, D. R.
Shaw, M. D., *see* McNamara, W. S.
Shen, K. C., and D. P. C. Fung, A New Method for Making Particleboard Fire-Retardant, 8:46 (No. 4786—$1.40)
Shunk, B. H., Development of an All-Weather, Fire-Retardant Treatment, 2:12 (No. 4682—$.80)
Siau, J. F., J. A. Meyer, and R. S. Kulik, Fire-Tube Tests of Wood-Polymer Composites, 7:31 (No. 4758—$1.20)
Sliker, A., Joist Deflections Simulated by a Computer Program, 9:71 (TN-238—$.60)
Soedel, W., *see* Reynolds, D. D.
Sprague, E. D., Wood Drying Review—1970, 2:17 (No. 4670—$1.00)
Sternitzke, H. S., and J. F. Christopher, Southern Timber Supply Trends and Outlook, 7:13 (No. 4846—$.80)
Stevens, R. R., *see* Thompson, W. S.
Still, S., J. B. Gartner, and T. D. Hughes, Effect of Sawdust Age and Nitrogen Application on Chrysanthemums Grown in White Oak Sawdust Media, 9:111 (No. 4810—$.80)
Strickler, M. D., *see* Pellerin, R. F.
Sturgeon, W. J., *see* Dobie, J.
Suchsland, O., Linear Hygroscopic Expansion of Selected Commercial Particleboards, 11:28 (No. 4825—$1.00)
Szymani, R., A Study of Corrugated Board Cutting by High Velocity Liquid Jet, 8:17 (No. 4697—$1.50)

T

Thompson, W. S., *see* Dust, J. V.
Thompson, W. S., and J. V. Dust, Pollution Control in the Wood-Preserving Industry. Part II. In-Plant Process Changes and Sanitation, 7:42 (No. 4777—$1.20)
Thompson, W. S., and J. V. Dust, Pollution Control in the Wood-Preserving Industry. Part III: Chemical and Physical Methods of Treating Wastewater, 12:25 (No. 4857—$1.00)
Thompson, W. S., and R. R. Stevens, Kiln Drying of Southern Pine Poles: Results of Laboratory and Field Studies, 3:17 (No. 4688—$1.50)
Troughton, G. E., and S.-Z. Chow, A Study on the Cause for Variation in Plywood Bond Quality with Open Assembly Time, 3:55 (No. 4669—$.80)
Troughton, G. E., J. F. Manville, and S.-Z. Chow. Lignin Utilization II—Resin Properties of 4-Alkyl Substituted Catechol Compounds, 9:108 (No. 4828—$.60)
Turkia, K., *see* Haygreen, J. G.

U

Unligil, H. H., Penetrability and Strength of White Spruce after Ponding 9:92 (No. 4779—$1.50)
Unligil, H. H., Tolerance of Some Canadian Strains of Wood-Rotting Fungi to Wood Preservatives, 1:40 (No. 4646—$1.20)

W

Wahlgren, H. E., *see* Okkonen, E. A.
Walser, D. C., An Instrument for Measuring Knife Height on Veneer Lathes, 3:59 (TN-226—$.40)
Walters, C. S., Weight as a Quality Control Factor in the Manufacture of Wood Ladder Rails, 8:30 (No. 4765—$.60)
Walters, E. O., Evaluation of Microwave and Nuclear Moisture Gages for Establishing Water Content Segregations, 2:52 (No. 4449—$1.20)
Weakley, F. B., and C. L. Mehltretter, Influence of Gluing Conditions on Performance of Crosslinked Protein Glue in Interior-Type Southern Pine Plywood, 1:45 (No. 4620—$1.20)
Wellwood, R. W., The Relevance of FPRS to the Small- and Medium-Size Wood Products Manufacturer, 9:40 (No. 4923—$.60)
Womack, R. J., *see* Graham, R. D.
Woodson, G. E., *see* McMillin, C. W.
Woodson, G. E., and C. W. McMillin, Boring Deep Holes in Southern Pine, 4:49 (No. 4700—$1.00)

Z

Zerrudo, J. V., *see* Laver, M. L.